NSN 5305-00-848-9284

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-848-9284 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.672 inches and 0.734 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Hole Diameter:** 0.036 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Hole Configuration Style:** Round longitudinal hole Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:**

Passivate

NSN 5305-00-848-9284

Socket Head Cap Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0