## NSN 5305-00-849-3795

Externally Relieved Body Screw - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5305-00-849-3795           |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.219 inches  |
| Fastener Length:  |
| 0.562 inches  |
| Head Style:   |
| Hexagon   |
| Head Height:  |
| Between 0.096 inches and 0.110 inches                                   |
| Width Between Flats:  |
| Between 0.244 inches and 0.250 inches                                   |
| First Diameter From Head:   |
| Between 0.120 inches and 0.125 inches                                   |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.344 inches  |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.164 inches  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Externally Relieved Body Diameter Quantity:                             |
| 1   |
| Material:   |
| Steel comp 303  |
| Material Specification:   |
| Qq-s-763 federal specification single material response                 |
| Surface Treatment:  |
| Passivate   |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

4000

A003b0