NSN 5305-00-849-7742

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-849-7742 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.187 inches **Fastener Length:** 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **Hole Diameter:** 0.047 inches First Diameter From Head: 0.118 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.438 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 70000 pounds per square inch **Hole Configuration Style:** Round longitudinal hole **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material:

Stainless steel

Material Specification:

Qq-s-763 federal specification single material response

NSN 5305-00-849-7742

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0