Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-849-9046

Thread Class:         2a         Thread Direction:         Right-hand         Thread Length:         0.126 inches         Fastener Length:         0.297 inches         Head Style:         Pan no. 2         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:         Between 0.072 inches and 0.082 inches         First Diameter From Head:         Between 0.100 inches and 0.105 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter:         0.171 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         40         Min. Tensile Strength (psi):         55000 pounds per square inch
Thread Direction:Right-handThread Length:0.126 inchesFastener Length:0.297 inchesHead Style:Pan no. 2Head Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesCross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):
Right-handThread Length:0.126 inchesFastener Length:0.297 inchesHead Style:Pan no. 2Head Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesHarensi (tpi):40Min. Tensile Strength (psi):
Thread Length:0.126 inchesFastener Length:0.297 inchesHead Style:Pan no. 2Head Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesHarensi Etternsi (tpi):40Min. Tensile Strength (psi):
0.126 inches Fastener Length: 0.297 inches Head Style: Pan no. 2 Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.072 inches and 0.270 inches First Diameter From Head: Between 0.100 inches and 0.082 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.171 inches Cross recess type 1 Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40
Fastener Length:0.297 inchesHead Style:Pan no. 2Head Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Oty Per Inch (tpi):40Min. Tensile Strength (psi):
0.297 inches Head Style: Pan no. 2 Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.072 inches and 0.082 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.171 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Kin. Tensile Strength (psi):
Head Style:Pan no. 2Head Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesHready Qty Per Inch (tpi):40Min. Tensile Strength (psi):
Pan no. 2 Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.072 inches and 0.082 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.171 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40
Head Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):
Between 0.256 inches and 0.270 inchesHead Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):
Head Height:Between 0.072 inches and 0.082 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):
Between 0.072 inches and 0.082 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.171 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
First Diameter From Head:Between 0.100 inches and 0.105 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.171 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):
Between 0.100 inches and 0.105 inches <b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b> 0.171 inches <b>Internal Drive Style:</b> Cross recess type 1 <b>Thread Diameter:</b> 0.138 inches <b>Thready Qty Per Inch (tpi):</b> 40 <b>Min. Tensile Strength (psi):</b>
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.171 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
0.171 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
Thread Diameter:         0.138 inches         Thready Qty Per Inch (tpi):         40         Min. Tensile Strength (psi):
0.138 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
40 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Externally Relieved Body Diameter Quantity:
1
haterial:
Steel
Surface Treatment:
Cadmium
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0