

View Online at <https://aerobasegroup.com/nsn/5305-00-850-3522>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.531 inches and 0.681 inches

**Fastener Length:**

Between 2.062 inches and 2.109 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.755 inches and 0.760 inches

**Shoulder Diameter:**

0.405 inches first shoulder and 0.406 inches first shoulder

**Shoulder Length:**

1.279 inches first shoulder and 1.301 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0