NSN 5305-00-850-3524

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-850-3524 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.641 inches **Fastener Length:** Between 1.875 inches and 1.922 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.756 inches and 0.760 inches **Shoulder Diameter:** 0.7556 inches first shoulder and 0.7604 inches first shoulder **Shoulder Length:** 1.240 inches first shoulder and 1.260 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch nse

Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4130
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment respor
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-850-3524 Shoulder Screw - Page 2 of 2



Fiig:

A003b0