NSN 5305-00-850-5301

Shoulder Screw - Page 1 of 2

3a

28

View Online at https://aerobasegroup.com/nsn/5305-00-850-5301



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.371 inches and 0.509 inches Fastener Length: Between 1.640 inches and 1.687 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.507 inches Shoulder Diameter: 0.264 inches first shoulder and 0.265 inches first shoulder Shoulder Length: 1.076 inches first shoulder and 1.098 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Shelf Life: Unit Of Measure:

Unf

N/a

NSN 5305-00-850-5301

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

