NSN 5305-00-850-5412

Shoulder Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-850-5412

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.372 inches	and 0.510 inches
Fastener Length:	
Between 1.828 inches	and 1.875 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.502 inches	and 0.507 inches
Shoulder Diameter:	
0.280 inches first shou	lder and 0.281 inches first shoulder
Shoulder Length:	
1.270 inches first shou	lder and 1.292 inches first shoulder
Internal Drive Style:	
High-torque	
Thread Diameter:	
0.250 inches	
Thready Qty Per Inch	(tpi):
28	
Min. Tensile Strength	(psi):
160000 pounds per squ	lare inch
Hardness Rating:	
36.0 rockwell c and 40).0 rockwell c
Countersink Angle:	
100.0 degrees	
Shoulder Shape:	
Round first shoulder	
Material:	
Steel comp e4340 or s	teel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp
4037 or steel comp 41	30
Surface Treatment:	
Cadmium and chroma	ie
Surface Treatment Sp	ecification:
Qq-p-416, type 2, cl 3	federal specification single treatment response
Thread Series Design	ator:
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5305-00-850-5412

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

