NSN 5305-00-850-5413



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-850-5413 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.371 inches and 0.509 inches **Fastener Length:** Between 1.952 inches and 1.999 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.506 inches **Shoulder Diameter:** 0.280 inches first shoulder and 0.281 inches first shoulder **Shoulder Length:** 1.395 inches first shoulder and 1.417 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130 **Surface Treatment:**

Surrace Treatment

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-850-5413

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0