NSN 5305-00-850-5426

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-850-5426

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.422 inches and 0.572 inches	
Fastener Length:	
Between 1.703 inches and 1.750 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.629 inches and 0.633 inches	
Shoulder Diameter:	
0.342 inches first shoulder and 0.343 inches first shoulder	
Shoulder Length:	
1.056 inches first shoulder and 1.078 inches first shoulder	
nternal Drive Style:	
High-torque	
hread Diameter:	
0.312 inches	
Fhready Qty Per Inch (tpi):	
24	
Ain. Tensile Strength (psi):	
160000 pounds per square inch	
lardness Rating:	
36.0 rockwell c and 40.0 rockwell c	
Countersink Angle:	
100.0 degrees	
Shoulder Shape:	
Round first shoulder	
Material:	
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or stee	el comp 4140 or steel comp
4037 or steel comp 4130	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2, class 2 federal specification single treatment response	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5305-00-850-5426

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

