NSN 5305-00-850-5427

Shoulder Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-850-5427

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.422 inche	es and 0.572 inches
Fastener Length:	
Between 1.765 inche	es and 1.812 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.629 inche	es and 0.633 inches
Shoulder Diameter	
0.342 inches first sh	oulder and 0.343 inches first shoulder
Shoulder Length:	
1.118 inches first sh	oulder and 1.140 inches first shoulder
Internal Drive Style	
High-torque	
Thread Diameter:	
0.312 inches	
Thready Qty Per In	sh (tpi):
24	
Min. Tensile Streng	th (psi):
160000 pounds per	square inch
Hardness Rating:	
36.0 rockwell c and	40.0 rockwell c
Countersink Angle	
100.0 degrees	
Shoulder Shape:	
Round first shoulder	
Material:	
Steel comp e4340 c	r steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp
4037 or steel comp	4130
Surface Treatment:	
Cadmium and chror	nate
Surface Treatment	Specification:
Qq-p-416, type 2, cla	ass 2 federal specification single treatment response
Thread Series Desi	gnator:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5305-00-850-5427

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

