

View Online at <https://aerobasegroup.com/nsn/5305-00-850-5841>

**Fastener Length:**

0.500 inches

**Head Style:**

Round

**Head Diameter:**

Between 0.264 inches and 0.285 inches

**Head Height:**

Between 0.099 inches and 0.111 inches

**Pilot Diameter:**

Between 0.122 inches and 0.126 inches

**Pilot Length:**

0.062 inches

**End Application:**

5895-01-514-7015, communications interface system (cis) (v) 2

**Features Provided:**

Casehardened

**Nonmachine Thread Style:**

Drive screw (type u)

**Nonmachine Thread Diameter:**

0.152 inches

**Product Name:**

Screw, drive, round head, type u, steel, carbon, cadmium plated

**Special Features:**

Screw is not recommended for use in material the thickness of which is less than one diameter of the screw

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Specification Data:**

80205 - nas-21318, 25 nov 1998 which replaced ms21318, rev a0./13/65 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0