

View Online at <https://aerobasegroup.com/nsn/5305-00-850-6257>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.532 inches and 0.682 inches

**Fastener Length:**

Between 1.000 inches and 1.047 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.756 inches and 0.760 inches

**Shoulder Diameter:**

0.389 inches first shoulder and 0.390 inches first shoulder

**Shoulder Length:**

0.209 inches first shoulder and 0.231 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0