

View Online at <https://aerobasegroup.com/nsn/5305-00-850-7621>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.446 inches and 0.512 inches

**Fastener Length:**

Between 1.501 inches and 1.531 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.717 inches and 0.760 inches

**Shoulder Diameter:**

0.389 inches first shoulder and 0.390 inches first shoulder

**Shoulder Length:**

0.711 inches first shoulder and 0.731 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp e4340 or steel comp 430 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1706 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0