## NSN 5305-00-855-2009

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-855-2009 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 4.785 inches **Head Style:** Hexagon **Head Height:** 0.125 inches Width Between Flats: 0.438 inches **First Diameter From Head:** 0.190 inches **Second Diameter From Head:** 0.147 inches **Third Diameter From Head:** 0.190 inches **Fourth Diameter From Head:** 0.147 inches Fifth Diameter From Head: 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.380 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.409 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.970 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 4.285 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi):

**Externally Relieved Body Diameter Quantity:** 

## NSN 5305-00-855-2009

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp 303
Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0