NSN 5305-00-856-0863

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-856-0863 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.135 inches **Fastener Length:** 0.620 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.312 inches **Head Height:** 0.380 inches **First Diameter From Head:** 0.170 inches **Second Diameter From Head:** 0.079 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.370 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.495 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303se **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-856-0863

Externally Relieved Body Screw - Page 2 of 2



H	nit	Ωf	M	eas	ur	Δ.
v		. 0	1414	-u3	uı	С.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.