NSN 5305-00-860-2065

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-860-2065 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Undercut pan no. 2 **Head Diameter:** Between 0.421 inches and 0.453 inches **Head Height:** Between 0.109 inches and 0.141 inches **Shoulder Diameter:** 0.201 inches first shoulder and 0.230 inches first shoulder **Shoulder Length:** 0.109 inches first shoulder and 0.141 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 302 or steel comp 316 or steel comp 303 or steel comp 303se **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A003b0

NSN 5305-00-860-2065

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.