NSN 5305-00-862-2000

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-862-2000 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.407 inches and 0.438 inches **Fastener Length:** 2.294 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.235 inches and 0.245 inches First Diameter From Head: Between 0.115 inches and 0.119 inches **Second Diameter From Head:** Between 0.139 inches and 0.145 inches **Third Diameter From Head:** Between 0.224 inches and 0.244 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.294 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.794 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.856 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** 3 **Product Name:** Navy special project **Special Features:** Furnished with washer on threaded end Material: Steel comp 430

Surface Treatment: Passivate

NSN 5305-00-862-2000

Externally Relieved Body Screw - Page 2 of 2



inread Series Designato
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0