

View Online at <https://aerobasegroup.com/nsn/5305-00-862-2003>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.344 inches and 0.376 inches

Fastener Length:

Between 1.516 inches and 1.578 inches

Head Style:

Fillister countersunk

Head Diameter:

Between 0.235 inches and 0.245 inches

Head Height:

Between 0.132 inches and 0.156 inches

First Diameter From Head:

Between 0.116 inches and 0.119 inches

Second Diameter From Head:

Between 0.139 inches and 0.145 inches

Third Diameter From Head:

Between 0.224 inches and 0.244 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.231 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.919 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.981 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

90.0 degrees

Externally Relieved Body Diameter Quantity:

1

Special Features:

Furnished w/one captivated flat cres washer

Material:

Steel comp 430

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0