

View Online at <https://aerobasegroup.com/nsn/5305-00-862-2005>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.407 inches and 0.438 inches

**Fastener Length:**

1.169 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.235 inches and 0.245 inches

**Head Height:**

0.144 inches

**First Diameter From Head:**

Between 0.115 inches and 0.119 inches

**Second Diameter From Head:**

Between 0.139 inches and 0.145 inches

**Third Diameter From Head:**

Between 0.224 inches and 0.244 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.200 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.669 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.731 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

45.0 degrees

**Externally Relieved Body Diameter Quantity:**

2

**Product Name:**

Navy special project

**Special Features:**

Furnished with washer on threaded end

**Material:**

Steel comp 430

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0