## NSN 5305-00-863-1850

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-863-1850 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.408 inches **Fastener Length:** 1.438 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.130 inches and 0.144 inches **First Diameter From Head:** 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.906 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 90 degrees of angle Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-00-863-1850

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0