NSN 5305-00-863-2574

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-863-2574 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.361 inches **Fastener Length:** 4.141 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.248 inches and 0.252 inches **Head Height:** 0.625 inches **First Diameter From Head:** 0.125 inches **Second Diameter From Head:** Between 0.248 inches and 0.252 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: **2.813 inches** Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.625 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-863-2574

Externally Relieved Body Screw - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.