NSN 5305-00-864-5443

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-864-5443 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** 4.875 inches **Head Style:** Flat chamfer **Head Diameter:** 0.281 inches **Head Height:** 0.156 inches **First Diameter From Head:** 0.187 inches **Second Diameter From Head:** 0.281 inches **Third Diameter From Head:** 0.187 inches **Fourth Diameter From Head:** 0.125 inches Fifth Diameter From Head: 0.187 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.219 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.344 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.891 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 1.001 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi):

Externally Relieved Body Diameter Quantity:

NSN 5305-00-864-5443

Externally Relieved Body Screw - Page 2 of 2



Special Features

0.144 in. Nom 6th diameter from head, 4.344 in nom lg from largest bearing surface to end of 6th dia

Material:

Stainless steel

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0