Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-864-5443

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.531 inches
Fastener Length:
4.875 inches
Head Style:
Flat chamfer
Head Diameter:
0.281 inches
Head Height:
0.156 inches
First Diameter From Head:
0.187 inches
Second Diameter From Head:
0.281 inches
Third Diameter From Head:
0.187 inches
Fourth Diameter From Head:
0.125 inches
Fifth Diameter From Head:
0.187 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.219 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.344 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
0.891 inches
Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:
0.961 inches
Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:
1.001 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
5

NSN 5305-00-864-5443

Externally Relieved Body Screw - Page 2 of 2



Special Features:

0.144 in. Nom 6th diameter from head, 4.344 in nom Ig from largest bearing surface to end of 6th dia

Material:

Stainless steel

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0