NSN 5305-00-866-7248

Setscrew - Page 1 of 2

Thread Class:

2a





Thread Direction: Right-hand Thread Length: Between 0.104 inches and 0.146 inches Fastener Length: Between 0.234 inches and 0.266 inches **Head Style:** Fillister **Head Diameter:** Between 0.297 inches and 0.328 inches **Head Height:** Between 0.148 inches and 0.180 inches Hole Diameter: 0.040 inches **Point Length:** Between 0.042 inches and 0.084 inches **Point Diameter:** Between 0.125 inches and 0.130 inches **Point Style:** Dog **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Hardness Rating: 43.0 rockwell c and 48.0 rockwell c Hole Configuration Style: Round Material: Steel **Material Specification:** Mil-s-7420 military specification single material response **Surface Treatment:** Phosphate

NSN 5305-00-866-7248

Setscrew - Page 2 of 2



Surface Treatment Specification:

Mil-c-16232, type 2 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7420 spec.