NSN 5305-00-869-4467

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-869-4467 **Thread Direction:** Right-hand Thread Length: 0.362 inches Fastener Length: Between 0.440 inches and 0.460 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.290 inches and 0.310 inches **Head Height:** Between 0.055 inches and 0.065 inches **Shoulder Diameter:** 0.186 inches first shoulder and 0.189 inches first shoulder **Shoulder Length:** 0.073 inches first shoulder and 0.088 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.187 inches **Nonstandard Thread Pitch Diameter:** +0.1643/+0.1667 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 286.0 brinell standard and 319.0 brinell standard **Shoulder Shape:** Round first shoulder Material: Stainless steel **Material Specification:** Ems 72614 fscm 73342 mfr ref single material response or ems 72620 fscm 73342 mfr ref single material response **Precious Material And Location:** External surface silver **Precious Material:** Silver **Surface Treatment:**

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Thread Series Designator:

Uns

NSN 5305-00-869-4467

Shoulder Screw - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0