

View Online at <https://aerobasegroup.com/nsn/5305-00-869-4467>

**Thread Direction:**

Right-hand

**Thread Length:**

0.362 inches

**Fastener Length:**

Between 0.440 inches and 0.460 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.290 inches and 0.310 inches

**Head Height:**

Between 0.055 inches and 0.065 inches

**Shoulder Diameter:**

0.186 inches first shoulder and 0.189 inches first shoulder

**Shoulder Length:**

0.073 inches first shoulder and 0.088 inches first shoulder

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.187 inches

**Nonstandard Thread Pitch Diameter:**

+0.1643/+0.1667 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

286.0 brinell standard and 319.0 brinell standard

**Shoulder Shape:**

Round first shoulder

**Material:**

Stainless steel

**Material Specification:**

Ems 72614 fscm 73342 mfr ref single material response or ems 72620 fscm 73342 mfr ref single material response

**Precious Material And Location:**

External surface silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0