

View Online at <https://aerobasegroup.com/nsn/5305-00-875-0749>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

0.375 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.156 inches and 0.172 inches

Internal Drive Style:

Slot

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

100000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel comp 302 or steel comp 303se or steel comp 304 or steel comp 316 or steel comp 303 or steel comp 304l or steel comp 305 or steel comp 316l

Screw Material Specification:

Qq-s-763 federal specification 1st material response or qq-s-764 cond a federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-764 cond a federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-s-763 federal specification 7th material response or qq-s-763 federal specification 8th material response

Screw Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0