Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-875-9836

| Thread Class: | |
|---|--------------------|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.203 inches | |
| Fastener Length: | |
| 0.814 inches | |
| Head Style: | |
| Pan no. 2 | |
| Head Diameter: | |
| Between 0.205 inches and 0.219 inches | |
| Head Height: | |
| Between 0.070 inches and 0.080 inches | |
| First Diameter From Head: | |
| 0.070 inches | |
| Distance From Largest Bearing Surface Of Head To End O | of First Diameter: |
| 0.557 inches | |
| Internal Drive Style: | |
| Cross recess type 1 | |
| Thread Diameter: | |
| 0.112 inches | |
| Thready Qty Per Inch (tpi): | |
| 40 | |
| Externally Relieved Body Diameter Quantity: | |
| 1 | |
| Special Features: | |
| Cone point at threaded end | |
| Material: | |
| Steel comp 302 | |
| Material Specification: | |
| Qq-s-763 federal specification single material response | |
| Surface Treatment: | |
| Passivate | |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| | |

NSN 5305-00-875-9836

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

