## NSN 5305-00-876-7972

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-876-7972 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.562 inches **Fastener Length: 4.735** inches **Head Style:** Flat chamfer **Head Diameter:** 0.312 inches **Head Height:** 0.203 inches **First Diameter From Head:** Between 0.145 inches and 0.150 inches **Second Diameter From Head:** 0.190 inches **Third Diameter From Head:** Between 0.145 inches and 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.719 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.969 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 3.204 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** Second diameter 10-32 unf 2a thd and one point 120 degrees of angle Material: Steel comp 303 **Material Specification:** 

Astm a582 assn standard single material response

**Surface Treatment:** 

**Passivate** 

## NSN 5305-00-876-7972

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0