

View Online at <https://aerobasegroup.com/nsn/5305-00-879-3825>

**Fastener Length:**

Between 0.219 inches and 0.281 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: submarine auxillary and miscellaneous systems; missile, minuteman lgm-30; chaparral/vulcan ads/ssamd; aircraft, orion p-3; shop equipment, contact maintenance, truck mounted; airborne mobile dir air spt ctl (2id), (02m jul83) (an/uyq-3a); trident hull structure; support equipment, b-1 aircraft; aircraft, stratolifter c-135; mixier rotary tiller

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Nonmachine Thread Diameter:**

0.112 inches

**Material:**

Steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1022 or steel comp 1030 or steel comp 1524

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0