

View Online at <https://aerobasegroup.com/nsn/5305-00-879-3825>

Fastener Length:

Between 0.219 inches and 0.281 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: submarine auxillary and miscellaneous systems; missile, minuteman lgm-30; chaparral/vulcan ads/ssamd; aircraft, orion p-3; shop equipment, contact maintenance, truck mounted; airborne mobile dir air spt ctl (2id), (02m jul83) (an/uyq-3a); trident hull structure; support equipment, b-1 aircraft; aircraft, stratolifter c-135; mixier rotary tiller

Nonmachine Thread Style:

Gimlet point (type a, ab or ba)

Nonmachine Thread Diameter:

0.112 inches

Material:

Steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1022 or steel comp 1030 or steel comp 1524

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0