## NSN 5305-00-880-8180

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-880-8180 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.325 inches **Fastener Length:** 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.078 inches and 0.080 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.213 inches **Secondary Washer Outside Diameter:** Between 0.213 inches and 0.223 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.013 inches and 0.223 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Steel comp 430 or steel comp 302 or steel comp 303se or steel comp 301 or steel comp 304 or steel comp 316 **Surface Treatment: Passivate Thread Series Designator:** 

Unc

## NSN 5305-00-880-8180

Assembled Washer Screw - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0