NSN 5305-00-880-8192

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-880-8192
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.231 inches
Fastener Length:
Between 0.280 inches and 0.312 inches
Head Style:
Pan
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.078 inches and 0.080 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.212 inches
Secondary Washer Outside Diameter:
Between 0.213 inches and 0.223 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
Between 0.025 inches and 0.031 inches
Secondary Washer Material Thickness:
0.013 inches
Material:
Steel comp 430 or steel comp 303se or steel comp 301 or steel comp 302 or steel comp 304 or steel comp 316
Material Specification:
Qq-s-763 federal specification 1st material response or mil-s-7720 military specification 2nd material response or mil-s-18732 military
specification 3rd material response or mil-s-5059 military specification 4th material response or mil-s-5059 military specification 5th material

response or mil-s-5059 military specification 6th material response or mil-s-5059 military specification 7th material response or mil-s-6721

Surface Treatment:

military specification 8th material response

Daccivate

NSN 5305-00-880-8192

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-s-7720 spec.