

View Online at <https://aerobasegroup.com/nsn/5305-00-880-8192>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.231 inches

**Fastener Length:**

Between 0.280 inches and 0.312 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.078 inches and 0.080 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Flat

**Primary Washer Outside Diameter:**

0.212 inches

**Secondary Washer Outside Diameter:**

Between 0.213 inches and 0.223 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

Between 0.025 inches and 0.031 inches

**Secondary Washer Material Thickness:**

0.013 inches

**Material:**

Steel comp 430 or steel comp 303se or steel comp 301 or steel comp 302 or steel comp 304 or steel comp 316

**Material Specification:**

Qq-s-763 federal specification 1st material response or mil-s-7720 military specification 2nd material response or mil-s-18732 military specification 3rd material response or mil-s-5059 military specification 4th material response or mil-s-5059 military specification 5th material response or mil-s-5059 military specification 6th material response or mil-s-5059 military specification 7th material response or mil-s-6721 military specification 8th material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-7720 spec.