NSN 5305-00-881-0705

Shoulder Screw - Page 1 of 2

3a

View Online at https://aerobasegroup.com/nsn/5305-00-881-0705



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.480 inches and 0.500 inches Fastener Length: Between 1.110 inches and 1.120 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.543 inches and 0.562 inches **Head Height:** Between 0.240 inches and 0.250 inches **Shoulder Diameter:** 0.371 inches first shoulder and 0.373 inches first shoulder Shoulder Length: 0.620 inches first shoulder and 0.630 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.187 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 32.0 rockwell c and 43.0 rockwell c Shoulder Shape: Round first shoulder Material: Steel comp 4042 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

18

NSN 5305-00-881-0705

Shoulder Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

