# NSN 5305-00-881-7648

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-881-7648



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.126 inches and 0.188 inches

#### Fastener Length:

Between 0.156 inches and 0.188 inches

#### **Head Style:**

Flat countersunk

### Head Diameter:

Between 0.233 inches and 0.279 inches

### Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.138 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

125000 pounds per square inch

## Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### Screw Material:

Steel comp 8630

### Screw Material Specification:

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

## Screw Surface Treatment:

Cadmium and chromate

### **Screw Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

#### **Special Features:**

Black unichrome dip, bulletin 65-8-cd

### **Thread Series Designator:**

Unc

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5305-00-881-7648

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

