NSN 5305-00-881-9336

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-881-9336 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.589 inches and 0.764 inches **Fastener Length:** Between 1.766 inches and 1.811 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.812 inches and 0.894 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A500d0

NSN 5305-00-881-9336

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.