NSN 5305-00-882-0629

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-882-0629 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.376 inches and 0.438 inches **Fastener Length:** 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.319 inches and 0.332 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Special Features:** Black unichrome dip, bulletin 65-8-cd **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-882-0629

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.