NSN 5305-00-882-9253

За

Thread Direction:

Right-hand

Thread Length:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-882-9253

Thread Class:

0.380 inches
Fastener Length:
0.440 inches
Head Style:
Fillister extended washer
Head Diameter:
0.375 inches
Head Height:
0.094 inches
Extended Washer Diameter:
0.437 inches
Extended Washer Thickness:
0.025 inches
Locking Feature:
Strip threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Hardness Rating:
32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material:
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification:
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment:
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium Surface Treatment Specification:
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator:
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator: Unf
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator: Unf Shelf Life:
Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a

NSN 5305-00-882-9253

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0