



View Online at <https://aerobasegroup.com/nsn/5305-00-882-9554>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.376 inches and 0.438 inches

Fastener Length:

0.438 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.072 inches and 0.082 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material Specification:

Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 1st material response or qq-w-405 federal specification 1st material response or qq-s-634 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-634 federal specification 18th material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416 type 2 class 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: