



View Online at <https://aerobasegroup.com/nsn/5305-00-882-9554>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.376 inches and 0.438 inches

**Fastener Length:**

0.438 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.072 inches and 0.082 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Screw Material Specification:**

Qq-s-630 federal specification 1st material response or qq-s-631 federal specification 1st material response or qq-w-405 federal specification 1st material response or qq-s-634 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634 federal specification 14th material response or qq-s-634 federal specification 15th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-634 federal specification 18th material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416 type 2 class 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

Fig: