NSN 5305-00-883-9304

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-883-9304

2aThread Direction:Right-handThread Length:1.750 inchesFastener Length:Between 2.656 inches and 2.750 inchHead Style:Flat countersunkHead Diameter:Between 0.249 inches and 0.279 inchInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreeScrew Material:Steel comp 430 or steel comp 302 or at strengthPassivateThread Series Designator:UncShelf Life:	
Right-handThread Length:1.750 inchesFastener Length:Between 2.656 inches and 2.750 inchHead Style:Flat countersunkHead Diameter:Between 0.249 inches and 0.279 inchInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesScrew Material:Steel comp 430 or steel comp 302 or steel	
Thread Length:1.750 inchesFastener Length:Between 2.656 inches and 2.750 inchHead Style:Flat countersunkHead Diameter:Between 0.249 inches and 0.279 inchInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesScrew Material:Steel comp 430 or steel comp 302 o	
Thread Length:1.750 inchesFastener Length:Between 2.656 inches and 2.750 inchHead Style:Flat countersunkHead Diameter:Between 0.249 inches and 0.279 inchInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesScrew Material:Steel comp 430 or steel comp 302 o	
 1.750 inches Fastener Length: Between 2.656 inches and 2.750 inch Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 430 or steel comp 302 or steel comp 302 or steel comp 430 or s	
Between 2.656 inches and 2.750 inch Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or steel Comp 430 or steel comp 302 or steel Screw Surface Treatment: Passivate Thread Series Designator: Unc	
Head Style:Flat countersunkHead Diameter:Between 0.249 inches and 0.279 inchInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesStreel comp 430 or steel comp 302 or	
Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degre Screw Material: Steel comp 430 or steel comp 302 or steel Screw Surface Treatment: Passivate Thread Series Designator: Unc	9S
Head Diameter: Between 0.249 inches and 0.279 inch Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or steel Screw Surface Treatment: Passivate Thread Series Designator: Unc	95
Between 0.249 inches and 0.279 inchInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):55000 pounds per square inchCountersink Angle:Between 80.0 degrees and 82.0 degreesScrew Material:Steel comp 430 or steel comp 302 or steel co	es
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degre Screw Material: Steel comp 430 or steel comp 302 or steel Screw Surface Treatment: Passivate Thread Series Designator: Unc	25
Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or steel comp 400 or steel comp 302 or steel	
Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or steel com	
0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degre Screw Material: Steel comp 430 or steel comp 302 or steel Screw Surface Treatment: Passivate Thread Series Designator: Unc	
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or steel	
32 Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degre Screw Material: Steel comp 430 or steel comp 302 or	
Min. Tensile Strength (psi): 55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degre Screw Material: Steel comp 430 or steel comp 302 or s Screw Surface Treatment: Passivate Thread Series Designator: Unc	
55000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degre Screw Material: Steel comp 430 or steel comp 302 or s Screw Surface Treatment: Passivate Thread Series Designator: Unc	
Countersink Angle: Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or steel comp	
Between 80.0 degrees and 82.0 degrees Screw Material: Steel comp 430 or steel comp 302 or s Screw Surface Treatment: Passivate Thread Series Designator: Unc	
Screw Material: Steel comp 430 or steel comp 302 or s Screw Surface Treatment: Passivate Thread Series Designator: Unc	
Steel comp 430 or steel comp 302 or a Screw Surface Treatment: Passivate Thread Series Designator: Unc	es
Screw Surface Treatment: Passivate Thread Series Designator: Unc	
Passivate Thread Series Designator: Unc	teel comp 316 or steel comp 303 or steel comp 303se
Thread Series Designator: Unc	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A500d0	