## NSN 5305-00-884-8708

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-884-8708

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.484 inches
Fastener Length:
0.593 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.371 inches and 0.385 inches
Locking Feature:
Patch threads or strip threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
85000 pounds per square inch
85000 pounds per square inch Countersink Angle:
Countersink Angle:
Countersink Angle: Between 99.0 degrees and 101.0 degrees
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life: N/a
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No