NSN 5305-00-888-8047

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-888-8047 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 5.188 inches **Head Style:** Pan **Head Diameter:** 0.226 inches **Head Height:** 0.081 inches **First Diameter From Head:** Between 0.151 inches and 0.156 inches **Second Diameter From Head:** Between 0.111 inches and 0.119 inches **Third Diameter From Head:** Between 0.151 inches and 0.156 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.341 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.375 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 4.626 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-00-888-8047

Externally Relieved Body Screw - Page 2 of 2



Inread Series Designato
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0