

View Online at <https://aerobasegroup.com/nsn/5305-00-889-2908>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.667 inches and 0.750 inches

Fastener Length:

0.750 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.442 inches and 0.507 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037

Screw Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-8503 military specification 4th material response or mil-s-5626 military specification 5th material response or ams 6300 assn standard 6th material response

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.