

View Online at <https://aerobasegroup.com/nsn/5305-00-889-2953>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.554 inches and 0.625 inches

**Fastener Length:**

0.625 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.473 inches and 0.492 inches

**Head Height:**

Between 0.162 inches and 0.175 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Screw Material:**

Steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037

**Screw Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-8503 military specification 4th material response or mil-s-5625 military specification 14th material response or ams 6300 assn standard 6th material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5000 spec.