NSN 5305-00-889-2990

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-889-2990



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.438 inches and 0.500 inches

Fastener Length:

0.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.306 inches and 0.313 inches

Head Height:

Between 0.103 inches and 0.118 inches

Hole Diameter:

0.038 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.190 inches

Hole Quantity:

2

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

140000 pounds per square inch

Hardness Rating:

Between 248.0 brinell standard and 321.0 brinell standard

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams 5735 assn standard single material response

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Head Hole Configuration Style:

Round

Thread Series Designator:

Unf

Specification Data:

80205-nas1101 professional/industrial association standard

NSN 5305-00-889-2990

Machine Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5002 spec.

