## NSN 5305-00-889-3060

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-889-3060 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.125 inches and 0.156 inches **Fastener Length:** Between 0.589 inches and 0.620 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.375 inches **Head Height:** 0.105 inches **First Diameter From Head:** 0.133 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.464 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 196000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 630 **Material Specification:** Ams5604 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response **Thread Series Designator:** Unf

Ch.

Shelf Life:

N/a

## NSN 5305-00-889-3060

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0