## NSN 5305-00-889-3088

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-889-3088

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 0.886 inches and 0.916 inches
Head Style:
Pan
Head Diameter:
Between 0.361 inches and 0.385 inches
Head Height:
Between 0.103 inches and 0.118 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.192 inches
Grip Length:
0.625 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1143 professional/industrial association standard

## NSN 5305-00-889-3088

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

